



HX 3000 C5

PORTABLE POWER

GENERATING SET Range INTENS

PRODUCT ADVANTAGES

- Solid and high-performance equipment
- Generating set guaranteed 3 years
- HONDA Professional Engine

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range INTENS

Equipment that is robust, long-lasting and simple to use for repetitive operations in difficult conditions.



This product meets the Qualigen charter, which aims to ensure a high level of quality and guarantee the safety of users. Qualigen: commitment to safety and quality.

HX 3000 C5

GENERAL SPECIFICATIONS

| | |
|--|--------------|
| Range | INTENS |
| Frequency (Hz) | 50 Hz |
| Max power (kW) * | 2.70 |
| Nominal voltage (V) | 230 |
| Number of Phase | Single phase |
| Fuel | Petrol |
| Tank (L) | 3.10 |
| 75% cons. (l/h) * | 1.30 |
| 75% Autonomy (h) * | 2.40 |
| Sound power level guaranteed LwA dB(A) | 95 |
| Acoustic pressure level @1m in dB(A) | 81 |
| Acoustic pressure level @7m in dB(A) | 67 |

ENGINE SPECIFICATIONS

| | |
|---|----------|
| Engine brand | HONDA |
| Engine type | GX200_C5 |
| Engine Type | O.H.V. |
| Start | Starter |
| Oil shutdown | Oui |
| Displacement (cm ³) | 196 |
| Oil system capacity including filters (l) | 0.60 |

ALTERNATOR SPECIFICATIONS

| | |
|--------------------------|-----------|
| Technology | Brushless |
| AVR Regulation | No |
| Indication of protection | IP 23 |
| Insulation class | H |

PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

DIMENSIONS AND WEIGHT

| | |
|-----------------|----|
| Length (cm) | 59 |
| Width (cm) | 46 |
| Height (cm) | 43 |
| Dry Weight (kg) | 41 |

PACKAGING

| | |
|------------------------------------|---------|
| Packaging type | Box |
| Length (cm) | 60.50 |
| Width (cm) | 46 |
| Height (cm) | 44 |
| Weight (kg) | 43 |
| Pallet type | 140/110 |
| Number of box by pallet | 15 |
| Pallet height (cm) | 145 |
| weight of the packaged Pallet (kg) | 661 |



5/19/2024

HX 3000 C5 - PORTABLE POWER - GENERATING SET INTENS

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



Funnel



User and maintenance manual

OPTIONS



This set includes the hour meter and the differential circuit breaker

This set includes the hour meter and the differential circuit breaker.



R05M - Manual source inverter for connecting a single-phase generator to a house

Manual source inverter for connecting a single-phase generator to a house



R06 - Trolley kit for HX 3000 / HXC 3000 ; Puncture-proof wheels Ø 187 mm

Trolley kit for HX 3000 / HXC 3000 ; Puncture-proof wheels Ø 187 mm



R18 - Maintenance kit for HX 3000 including oil, spark plug and air filter

Maintenance kit for HX 3000 including oil, spark plug and air filter



RBH1 - Box of 20 cans of 1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE

Box of 20 cans of 1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



RBHO-5 - Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE

Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm

Protective cover for HX(C) 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm



RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket

Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket



RPQ - 1m earth spike, supplied with 2m 10mm2 mains cable

1m earth spike, supplied with 2m 10mm2 mains cable