

HP 2.26 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Automatic priming
- Solid and high-performance equipment
- Offeres accessories
- High-pressure equipment

With nearly 6 bar of pressure, the HP 2.26 H can be used for high-pressure cleaning of machinery, such as agricultural vehicles. When combined with the nozzle kit, it can be used to suppress fires.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE SPECIALIST

High performance under extreme conditions.



HP 2.26 C5

WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	High voltage use
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	440
Outlflow maximum (m3/h)	26.40
Lifting height (m)	57
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3.10
75% cons. (l/h) *	0.90
75% Autonomy (h) *	3.40
Sound power level guaranteed LwA dB(A)	108
Acoustic pressure level @1m in dB(A)	92
Acoustic pressure level @7m in dB(A)	77

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (I)	0.60

DIMENSIONS AND WEIGHT

Length (cm)	41.50
Width (cm)	54.50
Height (cm)	45.50
Dry Weight (kg)	30

PACKAGING

Packaging type	Box
Length (cm)	54
Width (cm)	42
Height (cm)	45
Weight (kg)	35
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	148
weight of the packaged Pallet (kg)	430



HP 2.26 C5 - PORTABLE POWER - WATERPUMP AQUALINE SPECIALIST This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com



HP 2.26 C5

ACCESSORIES SUPPLIED



Inlet filter

Screw-on connectors



Circlips

User and maintenance manual

OPTIONS

RBH1 - Box of 20 cans of 1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE	Box of 20 cans of 1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE
RBHO-5 - Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE	Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE
RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm	5,70, Dimensions . 70 x 45 x 50 cm
F	1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE RBHO-5 - Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50



HP 2.26 C5 - PORTABLE POWER - WATERPUMP AQUALINE SPECIALIST This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528. SDMO Industries - 270 rue de Kerervem - CS 40047 - 29801 Brest cedex 9 – France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com