



XT 3.78 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- · HONDA Professional Engine
- Easy acces to the turbine (without tools)
- Automatic priming
- Resistant pump-barrel
- Offeres accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE SPECIALIST

High performance under extreme conditions.











XT 3.78 C5

WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	1340
Outlflow maximum (m3/h)	80.40
Lifting height (m)	27
Suction height (m)	8
Granulometry (mm)	27
Automatic priming	Yes
Fuel	Petrol
Tank (L)	5.30
75% cons. (I/h) *	2
75% Autonomy (h) *	2.70
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	94
Acoustic pressure level @7m in dB(A)	80

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX240_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	242
Oil system capacity including filters (I)	1.10

DIMENSIONS AND WEIGHT

Length (cm)	69
Width (cm)	48.50
Height (cm)	53.20
Dry Weight (kg)	58

PACKAGING

Packaging type	Box
Length (cm)	72
Width (cm)	52
Height (cm)	58
Weight (kg)	68.50
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	129
weight of the packaged Pallet (kg)	284



5/12/2024



XT 3.78 C5

ACCESSORIES SUPPLIED



Inlet filter



Circlips



OPTIONS

Screw-on connectors



User and maintenance manual



RHO - Protective cover for HX 3000 / HXC 3000 /

PERFORM 3000 - 3000 XL Protective cover for HX(C) 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 : 3,78 ; Dimensions : 70 x 45 x 50 cm

Dimensions: 70 x 45 x 50

cm



R12 - Piping kit for 3 water pumps made up of Piping kit for 3 water pumps made up of 5 m suction + 25 m lift. 5 m suction + 25 m lift