



TRASH 3 EXPORT

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

PRODUCT ADVANTAGES

- KOHLER air-cooled industrial engine
- Resistant pump-barrel
- Automatic priming
- Easy acces to the turbine
- Offeres accessories

Range AQUALINE SPECIALIST

High performance under extreme conditions.



TRASH 3 EXPORT

WATER PUMP SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	1083.33
Outflow maximum (m3/h)	65
Lifting height (m)	25
Suction height (m)	8
Granulometry (mm)	20
Automatic priming	Yes
Fuel	Diesel Fuel
Tank (L)	4.30
75% cons. (l/h) *	1.40
75% Autonomy (h) *	3.10
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	95
Acoustic pressure level @7m in dB(A)	81

ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	KD350
Engine Type	Diesel O.H.V.
Start	Starter
Oil shutdown	Non
Displacement (cm3)	349
Oil system capacity including filters (l)	1.20

DIMENSIONS AND WEIGHT

Length (cm)	71.50
Width (cm)	57
Height (cm)	59
Dry Weight (kg)	67

PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	59.50
Weight (kg)	79
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	132
weight of the packaged Pallet (kg)	326



5/9/2024

TRASH 3 EXPORT - PORTABLE POWER - WATERPUMP AQUALINE SPECIALIST

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 - France - Tél. +33 (0)2 98 41 41 41 - www.kohlersdmo.com

ACCESSORIES SUPPLIED



Inlet filter



Fast connections



Circlips



User and maintenance manual

OPTIONS



**RKB2 - Trolley kit for HX
4000 - 6000 - 7500T / HXC**

**4000 - 6000 - 7500T /
TECHNIC 10000 - 15000 /
VX 200/4 - 220-7,5 /**

**WELDARC 300 / TRASH ;
Puncture-proof wheels Ø
290 mm**

Trolley kit for HX 4000 - 6000 - 7500T / HXC 4000 - 6000 - 7500T / TECHNIC 10000 - 15000 / VX 200/4 - 220-7,5 / WELDARC 300 / TRASH ; Puncture-proof wheels Ø 290 mm



**RH1 - Protective cover for
HX 4000 - 6000 - 7500T /
HXC 4000 - 6000 - 7500T**

/ PERFORM 4500 - 4500

**XL - 5500T - 5500 T XL - 4500 XL - 5500T - 5500 T XL - 6500 - 6500 XL - 7500 T - 7500 XL
6500 - 6500 XL - 7500 T - 7500 XL / TECHNIC 6500 - 7500 TE / DIESEL / TRASH ; Dimensions : 82 x
7500 XL / TECHNIC 6500**

**- 7500 TE / DIESEL /
TRASH ; Dimensions : 82
x 58 x 50 cm**

Protective cover for HX(C) 4000 - 6000 - 7500T / PERFORM 4500 XL - 5500T - 5500 T XL - 4500 XL - 5500T - 5500 T XL - 6500 - 6500 XL - 7500 T - 7500 XL 6500 - 6500 XL - 7500 T - 7500 XL / TECHNIC 6500 - 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm